

MY 2-IN-1 EYE LINER & SHADOW

14.237.01 C152

- Claims:**
- Multi-use product
 - Light and cool gel-cream texture
 - Silicone-like skin feel
 - Active makeup

PHASE	INGREDIENT	INCI NAME	SUPPLIER	%
A	Deionized Water	Water	-	74.60
	Dermofeel® PA-3	Sodium Phytate (and) Water (and) Alcohol	Dr Straetmans	0.10
	Blanc Covasop W9775	CI 77891 (and) Propylene Glycol (and) Silica	Sensient® Cosmetic Technologies	3.00
	Black Covasop W9774	CI 77499 (and) Propylene Glycol (and) Silica	Sensient® Cosmetic Technologies	0.60
	PVP/VA64 Cosmetic Grade Ecogel™	PVP/VA Copolymer Lysolecithin (and) Sclerotium Gum (and) Xanthan Gum (and) Pullulan	Nanhang Lucas Meyer Cosmetics	0.50 2.50
B	Shercemol® PDD	Diisostearoyl Polyglyceryl-3 Dimer Dilinoleate	Lubrizol	2.00
	Vitapherole® E1000	Tocopherol (and) Helianthus Annuus (Sunflower) Seed Oil	VitaeNaturals	0.20
	Cetiol® CC	Dicaprylyl Carbonate	BASF	2.00
	Alphaflow® 30	Hydrogenated Polydecene	Aiglon	2.00
	Koboguard 5400 IDD	Hydrogenated Polycyclopentadiene (and) Isododecane	Kobo	1.00
C	KTZ® Misterioso Pewter	Mica (and) Titanium Dioxide (and) Iron Oxides (C.I. 77499)	KOBO	8.00
	Capixyl™	Butylene Glycol (and) Water (and) Dextran (and) Acetyl Tetrapeptide-3 (and) Trifolium Pratense (Clover) Flower Extract	Lucas Meyer Cosmetics	2.50
	Verstabil PC	Phenoxyethanol (and) Caprylyl Glycol	Dr Straetmans	1.00

Manufacturing Procedure:

1. Mix the ingredients of phase A and heat up to 75°C. Maintain under stirring (1200 rpm) for about 30 minutes.
2. Prepare phase B: mix the ingredients of phase B and heat up to 75°C.
3. Pour phase B into phase A and homogenize under maximum stirring (rotor stator, 7200 rpm for 2 minutes).
4. Cool down to room temperature and add the ingredients of phase C

Formula Specifications:

Aspect: Silver gel cream
 Viscosity (Rheo ELV 8, spindle 4, 6 rpm, 3 mn): 20 000 - 30 000mPa.s
 pH: 6.5 - 7.0
 Preservative efficacy test: Pass
 Pilot batch: 6 kg

Stability Tests: On lab batch up to 1kg
 Up to 1 month at 50°C
 Up to 3 months at: Room Temperature, 4-8°C and 45°C
 Centrifugation (3000 rpm, 20 mn): Stable